

7006 多通道扩展器



7006 系列多通道扩展器可搭配 ESA 与 SE 系列组成多点测试功能，可弹性组合成不同测试模块，亦可增加待测物 (DUT) 数量，解决复杂配线操作困难，提升测试效率增加产能。

产品特点

- 最大可提供 80 个输出通道供测试切换 (1 台 master 搭配 4 台 slave)。

7006 产品规格

型号	7006
输入电源	
电压	N/C
高电压通道 (H.V)	5kVac/6kVdc
高电流通道 (H.A.)	40Aac
标准模组	1 module (8 H.V. channels)
最多可安装模组	Maximum 2 models can be mounted
选购模组	1 module can be mounted in addition to the standard module Either 8 H.V. or 8 H.A. modules can be selected from Optional items
一般规格	
控制模组 (选购)	Include GPIB or USB & RS232 Interface and Power module (Input Power 115V/230Vac \pm 15%, 50Hz/60Hz \pm 5%, max. current 2A)
多台连机	7006 + Master module acts as master to control slave units (Max 4 units) This makes this system total 80 channels. (16ch/unit x 5 units = 80 ch)
操作温度 / 储存温度 / 湿度	0 to 40°C/-40 to 75°C/20 to 80%RH
尺寸 (宽 x 高 x 深), mm	430 x 89 x 300
重量	9.5kg Max.

标准配件

1105 Hipot and Scanner Linking Lead*1; 1109 Hipot Output Lead - Pin Connector*8; 1111 External Scanner Communication Cable*1

*Product specifications are subject to change without notice

产品型号

- 7006 Matrix Scanner (8 H.V. scanner inclusive as standard)

选购功能

- OPT.743 8 H.V. channels module for AC-W/DC-W or IR testing
- OPT.744 8 H.A. channels module for Ground Bond testing
- OPT.791 Master module with GPIB Interface
- OPT.792 Master module with USB & RS232 Interface
- OPT.7032 7kVac/8kVdc Output Function

Note: 1. OPT.791 & OPT.792 are mutually exclusive, only one Option can be selected.
2. OPT.743, OPT.744 & OPT.7032 only one option can be selected.